



NOTE :

1. Freq : 2.4~2.5GHz & 4.9~5.825GHz
2. Gain : 2 dBi
3. Gain Deviation : ± 0.5 dBi
4. SWR : 2 Max
5. Pattern : Omni
6. Flammability Class : UL-94 HB

TOLERANCES

DIMENSIONS ARE IN MILLIMETER

UNLESS OTHERWISE SPECIFIED

.X	±0.2
.XX	±0.1
.XXX	±0.05
ANGLES	±5°

TITLE

2.4G & 5.8G 2 dBi 天線

PART NO.

AS103-F

DRAWN NO.

FILE PATH:



SOCAA CORP.,LTD.

(Solution Of Connector & Antenna)

APPROVED *Pony* DATE 02.09.15

CHECKED *Alvin* DATE 02.09.15

DRAWN *Elvis* DATE 02.09.15

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWN NO.
7	COPPER COVER	BRASS	NICKEL	1	M-0201
6	COPPER COVER	BRASS	NICKEL	1	M-0139
5	COVER	PU	BLACK	1	I-0114
4	RESOLVER	NYLON	NONE	1	I-0115
3	RG178U(50mm) CABLE	ABS-757	BROWN	1	CT-0064
2	BASE FOR CONNECTOR	ABS-757	BLACK	1	I-0116
1	R19-60-8-178U-50	T.G.N/B.C		1	R19-0127